

Features and Benefits



- NEW friction stay compliments the Living range window handle, door handle and door hinges.
- BBA Approved.
- Available in 8", 10", 12", 16", 20" and 24" Top hung.
- Side hung variations in 12" and 16".
- BSEN ISO 9001/2008 Quality Management System.

Technical Information

Size Ins		Size MM	Application	Window Size Approx Width MM	Window Size Approx Height MM	Window Weight Approx	Stack Height MM	Opening Angle
8	*	210	Top Hung	1200	300	12	13/14 & 16/17	60
10	*	260	Top Hung	1200	450	14	13/14 & 16/17	60
12		311	Top Hung	1200	600	16	13/14 & 16/17	90
16		406	Top Hung	1200	750	20	13/14 & 16/17	65
20		511	Top Hung	1200	900	24	13/14 & 16/17	50
24		615	Top Hung	1200	1500	27	13/14 & 16/17	50
12		311	Side Hung	650	1250	22	13/14 & 16/17	55
16		406	Side Hung	700	1300	24	13/14 & 16/17	65

Assessment Data

Performance: 30,000 cycle guarantee.
Corrosion resistance Austenitic: 240 Hours.
Corrosion resistance Ferretic: 90 Hours.

Additional Information

Box Qty: 25 Pairs.
Items Marked * boxed in 50's.

It is the responsibility of the window manufacturer to ensure that the finished window meets any required safety and performance specifications.

WINLOCK

Unit B, Hortonwood 31, Telford, Shropshire, TF1 7GS
Tel:01952 602250 Fax:01952 602255.
Email:sales@winlock.co.uk Web:www.winlock.co.uk