

Living

Features and Benefits



- ▣ Initial opening similar to standard side hung friction stay.
- ▣ Full opening to 90 degrees providing clear egress in excess of 500mm on a 600mm wide vent.
- ▣ Available in 13mm and 17mm stack heights.
- ▣ Easy to operate thumb catches allow the vent to slide to the 'Easy Clean' position giving between 100mm and 250mm clear opening (SP312/16EZ).
- ▣ To rest simply close the window and then re-open to go back to the egress position and close.
- ▣ Available in Austenitic & Ferretic stainless steel.
- ▣ Manufactured in the UK.
- ▣ BSEN ISO 9001/2008 Quality Management System.

Technical Information

Size Inches	Size MM	Application	Window Size Approx Width MM	Window Size Approx Height MM	Window Weight Approx	Stack Height MM	Opening Angle
16	413	Side Hung	600	1200	21	13 & 17mm	89 Deg
12	311	Side Hung	600	1200	18 or 21 with a Riser	13 & 17mm	85 Deg

Additional Information

Box Qty: 25 pcs per box

Assessment Data

Conforming to all current British Builings Standards and Fensa requirments.

When fitting the Egress/Easy Clean please observe. BS8213 Part 1: 1991 code of practice for safety in use and during cleaning windows.

Please Note: It is the responsibility of the window manufacturer to ensure that the finished window meets any required safety and performance specifications.

WINLOCK

Halesfield 8, Telford, Shropshire, TF7 4ES.

Tel: 01952 680178 Fax: 01952 684355

Sales: 01952 686777

Email: sales@winlock.co.uk

Web: www.winlock.co.uk

